

JEM ZR35 Fog machine

The JEM™ ZR35 is a mid-sized fog machine designed to deliver superior and uninterrupted performance in demanding professional applications. Via its powerful 1,500 W heat exchanger, the JEM ZR35 produces a fantastic peak output ideal for mid to large-sized venues and stages in both install and rental markets.



General

The rugged yet weight optimized JEM ZR35 also features variable output control for more subtle effects and is fully up-to-date with digital remote, DMX and RDM. The entire JEM ZR range is compatible with a wide range of JEM Pro fog fluids. As machines designed and built to last, the JEM ZRs will continue to perform with great output and low consumption.

Features

- 1,500 W heat exchanger
- 50 ml in 30 seconds peak performance
- 800 m3/min fog output
- variable output control for subtle effects
- 8-9 minute warm-up time
- digital remote, DMX and RDM
- compatible with a wide range of JEM Prof fog fluids
- floor standing or truss mounting (bracket included)
- powerCON TRUE1
- 4-liter bottle (also compatible with a 5-liter bottle)

TECHNICAL SPECIFICATIONS

Dimensions	590 (l) x 395 (w) x 264 (h) mm
Weight, dry	15.5 kgs
Weight, filled	19.1 kgs
Coverage volume	800 m3 per minute
Fluid consumption	140 ml per minute
Control options	integrated digital remote control, DMX, optional: analog remote control
Control parameters	continuous or timer-controlled output
Fog	variabele output control, 0-100%
Installation	mounting: standing or hanging
AC power	220-240 V nominal, 50/60 Hz
Max. ambient temperature	40° C
Construction	Housing: Steel & aluminium, color: black
Approvals	EN 60335-1+A15, EN 62233, EU EMC: EN 61000-6-3, EN 61000-6-1



JEM ZR35 Fog machine
The most specified fog machine in the world