

Oxylog® VE300 Emergency and Transport Ventilation

The straightforward and user-friendly Dräger Oxylog® VE300 is built to face your challenges in preclinical emergency services. With reliable ventilation technology, robustness and intuitive operation, it provides you with reliable and safe assistance in an emergency.



D-20047-2020

Benefits

Simple, ergonomic, robust – and economical:

- Reliable even under extreme operating conditions (-20 to +50°C)
 - Three step device start up, takes less than 10 seconds
 - Device check takes less than a minute
 - Preset parameters for fast ventilation start (adult, child, infant)
 - Replaceable and rechargeable battery for up to 9 hours of operation
 - Low oxygen consumption thanks to DuroFlow technology*
 - Clear user guidance with moderate training time
 - Easily accessible documentation with Bluetooth and USB interface: patient data, system test, screen shots
 - Wall mount permits flexible positioning
 - Practical extras available as options: belt, stretcher mounting, accessory bag, battery charger
 - Ergonomic carrying handle directly above the device's centre of gravity
-

Easy to carry, quick-start ventilation

- Clear colour touch screen
- Flip-screen button rotates the display 180°
- Volume-controlled ventilation: VC-CMV / VC-AC, VC-SIMV
- Pressure-controlled ventilation: PC-BIPAP**
- Spontaneous breathing support: SPN-CPAP/PS with NIV
- Pressure support: PS
- CPR mode can be selected with a single keystroke
- For patients with a tidal volume of 50 mL upward
- Capnography: main-stream CO₂ measurement
- Logbook supports documentation

*DuroFlow technology: based on the "Venturi-Principle" without additional base flow

** trademark used under license

Related Products



MT-5809-2008

Dräger Oxylog® 3000 plus

Offering high ventilation performance with features such as AutoFlow® integrated capnography and non-invasive Ventilation, the compact and robust Oxylog® 3000 plus helps you transport your patients safely and provides feedback on correctness of intubation and ventilation effectiveness. The Oxylog® 3000 plus gives you confidence to master even the most demanding situations.

Technical Data

Device specifications

Dimension (W x H x D)	
Main device	399 x 153 x 160 mm (15.7 x 6.8 x 6.3 inches)
Main device, with carrier system	607 x 228–251 x 166 mm (23.9 x 9.0–9.9 x 6.5 in)

Weight

Main device, without battery	Approx. 3.3 kg (7.3 lb)
Main device, with battery	Approx. 3.6 kg (7.9 lb)
Main device, with carrying system, battery and bag	Approx. 5.6 kg (12.4 lb)

Screen

Technology	TFT colour screen
Size	4.3 inch

External connections

USB	2.0 Only connect passive storage media, i.e. devices that do not have a separate power supply.
-----	--

Sound pressure level (SPL)

Average sound pressure level Leq(A) (free-field measurement at a distance of 1 m in accordance with ISO 3744 and during typical ventilation)	≤45 dB(A)
Sound pressure level L(A) of alarm signals (measured according to IEC 60601-1-8)	Approx. 47 to 83 dB(A), depending on alarm priority

Ambient conditions

During operation

Temperature (device)	-20°C to +50°C (-4° to +122°F)
Temperature (power supply)	0°C to +50°C (+32°F to +122°F)
Permissible operating temperature during charging	0 to +45°C (+32 to +113°F)
Ambient pressure (device)	620 to 1,100 hPa (8.99 to 15.95 psi) Automatic ambient pressure compensation within this pressure range
Height above sea level	Up to 4,000 m (13,123 feet)
Ambient pressure (power supply)	700 to 1,060 hPa (10.15 to 15.37 psi)
Relative humidity	5 to 95% (without condensation)

Settings

Ventilation modes	VC-CMV, VC-AC, SPN-CPAP
Optional	VC-SIMV/PS, PC-BIPAP, SPN-CPAP/PS
Respiratory rate RR	Adult: 2 to 30 /min (VC-SIMV, PC-BIPAP) Adult: 5 to 30 /min (VC-CMV, VC-AC) Adult: 10 to 30 /min (during apnea ventilation) Child: 2 to 50 /min (VC-SIMV, PC-BIPAP) Child: 10 to 50 /min (VC-CMV, VC-AC) Child: 10 to 50 /min (during apnea ventilation) Infant: 2 to 50 /min (VC-SIMV, PC-BIPAP) Infant: 10 to 50 /min (VC-CMV, VC-AC) Infant: 10 to 50 /min (during apnea ventilation)
Maximum airway pressure Pmax	20 to 60 mbar (20 to 60 cmH ₂ O)
Ratio of inspiration time to expiration time I:E	1:4 to 4:1
Inspiration time Ti	0.3 to 10 s
Tidal volume VT, VTapn	Adult: 0.3 to 2.0 L, BTPS

Technical Data

	<p>Child: 0.1 to 0.4 L, BTPS Infant: 0.05 to 0.2 L, BTPS Measurements referred to conditions of the patient's lungs, body temperature 37 °C (98.6 °F), ambient pressure, water vapor saturated gas.</p>
O ₂ concentration	<p>100% O₂ and O₂/air mix Actual value depends on inspiratory flow and mean airway pressure.</p>
Positive end-expiratory pressure PEEP	0 to 20 mbar (0 to 20 cmH ₂ O)
Trigger sensitivity (flow trigger)	Off or 3 to 15 L/min
Trigger sensitivity (pressure trigger)	Off or 3 to 15 steps
Pressure support ΔP _{supp}	0 to 35 mbar (0 to 35 cmH ₂ O) (relative to PEEP)
Pressure rise time for pressure support	slow (1 s), standard (0.4 s), fast (<0.4 s)
Regions of alarm limits	
MVe upper alarm limit	1.2 to 60 L/min
MVe lower alarm limit	0.2 to 40 L/min
RR upper alarm limit	10 to 99 /min
etCO ₂ upper alarm limit	5 to 99 mmHg / 0.5 to 13.2 kPa / 0.5 to 13.2 vol%
etCO ₂ lower alarm limit	0 to 94 mmHg / 0 to 12.7 kPa / 0 to 12.7 vol%
Performance data	
Control principle	Time-controlled, volume-constant, pressure-supported
Maximum inspiratory flow	100 L/min ¹
Device compliance	
with 1.5 m breathing tube	< 1.5 mL/mbar (1.5 cmH ₂ O)
with 3.0 m breathing tube	< 2 mL/mbar (2 cmH ₂ O)
Inspiratory resistance with breathing circuit	<p>Adult, with adult breathing hose ≤5 mbar (5 cmH₂O) at 60 L/min Child, with adult breathing hose ≤3 mbar (3 cmH₂O) at 30 L/min Infant, with pediatric breathing hose ≤1.5 mbar (1.5 cmH₂O) at 30 L/min</p>
Expiratory resistance with breathing circuit	<p>Adult, with adult breathing hose ≤6 mbar (6 cmH₂O) at 60 L/min Child, with adult breathing hose ≤4 mbar (4 cmH₂O) at 30 L/min Infant, with pediatric breathing hose ≤5 mbar (5 cmH₂O) at 30 L/min</p>
Emergency air valve	Opens the breathing system upon failure of the gas supply, permits spontaneous breathing with ambient air
Safety valve	Opens the breathing system in the event of device malfunction to approximately 80 mbar (80 cmH ₂ O)
<p>¹ At supply pressure > 350 kPa (50.76 psi). At a supply pressure < 350 kPa (50.76 psi), the maximum inspiratory flow is reduced to 80 L/min, at a supply pressure < 280 kPa (40.61 psi) to 39 L/min</p>	
Displayed measured values	
Airway pressure measurement	
Display range	0 to 100 mbar (0 to 100 cmH ₂ O)

Technical Data

Resolution	1 mbar (1 cmH ₂ O)
Accuracy	±(2 mbar (2 cmH ₂ O) +8% of measured value)
Flow measurement	
Minute volume MVe	
Display range	0 to 100 L/min, BTPS
Resolution	0.1 L/min
Accuracy	± 20% of measured value or ± 0.4 L/min, whichever greater
Tidal volume VTe	
Display range	0 to 5,000 ml, BTPS
Resolution	1 mL
Accuracy	± 20% of measured value or ± 20 ml, whichever greater (adult breathing hose) ± 20 % of the measured value or ± 15 mL, whichever greater (pediatric breathing hose)
CO₂ measurement (option)	
Measurement principle	Mainstream system
Display range	0 to 100 mmHg / 0 to 13.2 vol% / 0 to 13.3 kPa
Resolution	1 mmHg / 0.1 vol% / 0.1 kPa
Respiratory rate measurement	
Display range	0 to 99 /min
Resolution	1 /min
Accuracy	±1 /min
Waveform display	
Airway pressure Paw (t)	0 to 90 mbar (0 to 90 cmH ₂ O)
Flow (t)	-150 to 150 L/min
CO ₂	0 to +100 mmHg / 0 to +15 vol% / 0 to +15 kPa
Monitoring	
Expiratory minute volume MVe (option)	
Alarm, upper alarm limit	If the upper alarm limit has been exceeded
Setting range	1.2 to 60 L/min
Alarm, lower alarm limit	If the value has fallen below the lower alarm limit
Setting range	0.2 to 40 L/min
Alarm delay	40 seconds after start of ventilation
Apnoea	
Alarm	If no breathing activity is detected for >15 seconds and Tapn is switched off
Apnea alarm time Tapn	
Alarm	If no breathing activity is detected Setting range: Off or 15 to 60 seconds
Respiratory rate RR	
Alarm, upper alarm limit	If the upper alarm limit has been exceeded
Setting range	10 to 99 /min
Alarm delay	30 seconds after start of ventilation

Technical Data

End expiratory CO₂ concentration – etCO₂ (option)

Alarm, upper alarm limit	If the upper alarm limit has been exceeded
Setting range	5 to 99 mmHg / 0.5 to 13.2 kPa / 0.5 to 13.2 vol%
Alarm delay	30 seconds after connection and calibration
Alarm, lower alarm limit	If the value has fallen below the lower alarm limit
Setting range	0 to 94 mmHg / 0 to 12.7 kPa / 0 to 12.7 vol%
Alarm delay	30 seconds after start of ventilation, connection and calibration

Leakage

Alarm	Only for Plus option in VC modes and deactivated NIV in CPAP: If VT _e < 45% of VT _i
Alarm delay	30 seconds after start of ventilation

Disconnection

Alarm	If disconnection of the breathing circuit is detected
Alarm delay	30 seconds after start of ventilation

Data communication (option)

Exported data	Measured values Waveforms Alarm messages Alarm settings User settings System test information Screenshots
---------------	---

Operating data

Power supply

Input Voltage	19 V + 5/-3 VDC Power supplies (power supply unit and DC converter) are specified as parts of the Oxylog® VE300.
Duration of operation	With new and fully charged battery, without external power supply: <ul style="list-style-type: none"> – 8 hours with typical ventilation (VC-CMV, RR = 12/min, VT = 500 mL, PEEP = 5 mbar (5 cmH₂O), I:E = 1:2) – 9 hours (without CO₂ sensor and at reduced screen brightness)
Power consumption	During charging: max. 2.0 A at 19 VDC During typical ventilation: max. 0.8 A at 19 VDC
Battery type	Lithium-ion battery
Charging time	Approx. 5 hours The specified charging time applies when recharging the battery completely after it has been depleted.

Power supply unit

Protection class (as defined in IEC 60601-1)	Class II
Degree of protection	IP22
Input	100 to 240 V~ / 50/60 Hz / 1.0 A
Output	19 V / 4.47 A (0 to +40°C (32 to +104°F)) / 3.57 A (+40 to +50°C (+104 to 122°F)) To disconnect the ventilator from the power supply, disconnect the power cable from the power socket.

Technical Data

Fuses F1 and F2	The power supply unit is intended for indoor use only (e.g. in hospitals or fire stations). T 2.5 AH/ 250 V~
Gas supply	
Oxygen supply pressure	From a central gas supply system or an oxygen cylinder 270 to 600 kPa (39 to 87 psi)
Gas characteristics	Medical oxygen, 93% oxygen
Connection to the oxygen supply:	NIST (Non-Interchangeable Screw-Threaded) according to EN 739 / ISO 5359 or DISS (Diameter Index Safety Systems) according to CGA V5-1989 or NF (Norme française) S90-116 Specific quick connection

Not all products, features, or services are for sale in all countries.
Mentioned Trademarks are only registered in certain countries and not necessarily in the country in which this material is released. Go to www.draeger.com/trademarks to find the current status.

CORPORATE HEADQUARTERS
Drägerwerk AG & Co. KGaA
Moislinger Allee 53–55
23558 Lübeck, Germany
www.draeger.com

Manufacturer:
Drägerwerk AG & Co. KGaA
Moislinger Allee 53-55
23542 Lübeck, Germany

REGION EUROPE
Drägerwerk AG & Co. KGaA
Moislinger Allee 53–55
23558 Lübeck, Germany
Tel +49 451 882 0
Fax +49 451 882 2080
info@draeger.com

REGION MIDDLE EAST, AFRICA
Drägerwerk AG & Co. KGaA
Branch Office
P.O. Box 505108
Dubai, United Arab Emirates
Tel +971 4 4294 600
Fax +971 4 4294 699
contactuae@draeger.com

REGION ASIA PACIFIC
Dräger Singapore Pte. Ltd.
61 Science Park Road
The Galen #04-01
Singapore 117525
Tel: +65 6872 9288
Fax: +65 6259 0398
asia.pacific@draeger.com

**REGION CENTRAL
AND SOUTH AMERICA**
Dräger Panamá Comercial
S. de R.L.
59 East Street, Nuevo Paitilla,
House 31, San Francisco Town
Panama City, Panama
Tel +507 377-9100 / Fax -9130
servicioalcliente@draeger.com

Locate your Regional Sales
Representative at:
www.draeger.com/contact

